

L. P.	wymiar w mm szer. x wys.		Dodatkowe	Cylinder / ilość zębów	Ilość etykiet w rzędzie
	X	Y			
1	7	150	U / min. 2R	96	6
2	10	10	P - (□ w polu)	68	6
3	10	12	PK / min. 2rz	66	6
4	10	100	U	65	6 / 7
5	10	100	U - perf.	65	6 / 7
6	12	14	F	65	6 / 7
7	15	5	U - J-407 *	65	6 (2x3R)
8	15	7	U - J-407 *	65	6
9	15	15	F, black mark 2,5 mm	68	4
10	15	40	U	68	6
11	15	60	U	79	6
12	17	90	U	88	4
13	19	22	U	78	5
14	20	10	P	67	4 (2x2R)
15	20	10	P/F black mark 2,5 mm		4
16	20	10	F - J-407 *	67	4 (2x2R)
17	20	20	U	78	4
18	20	40	P - odstęp między rzędami 40mm	67	2
19	20	80	F	78	6
20	21	40	U	68	6 i 7
21	22	7	P	68	6
22	22	50	P	67	6
23	23	12,3	U	67	4
24	23	120	U	78	6
25	23	150	P	96	6,7
26	25	15	F - J-407 *	65 / 66	4 (2x2R)
27	25	15	U	66	4
28	25	25	U	78	6
29	25	25	U - perf. etykiety po szer.	78	2
30	25	25	P black mark 3mm	78	
31	25	35	U	85	3
32	25	40	U	67	6
33	25	75	U	74	6
34	25	80	U	78	6
35	26	9	F	65	6
36	26	14	P	68	6
37	26	21	F, owal	96	6
38	30	11	U	65	3
39	30	11	F - J-407 *	65	3
40	30	12	U	65	6
41	30	12	F - nacięcia etykiet wokół	65	3
42	30	15	U	67	3 / 6
43	30	17	U	65	6
44	30	20	P	65	4 / 6
45	30	20	P / TYRE 10 tys.	65	6
46	30	30	F	74	6
47	30	30	U / perf. pion	82	6
48	30	40	P	67	6
49	30	60	U	99	6
50	30	80	P	79	6
51	30	127,5	P	82	6
52	30	180	P	115	6

53	31	22	T	79	4
54	32	15	U	67	6
55	32	20	U / TYRE 10tys.	78	6
56	32	20	U/F (PK)	78	7
57	32	25	U	95	6
58	32	35	P	95	6
59	32	40	U	82	6
60	33,3	254	KA - karton perf, specj. /pętelki, faworki	80	3
61	34	20	U	65	3
62	34	70	P	114	6
63	33	16	F	65	4
64	35	14	F	65	2
65	35	25	P	95	6
66	35	30	P	95 / 82	6
67	35	40	P	67	6
68	35	50	U (PK)	67	6
69	35	59	P	78	6
70	35	243	P / 4,65 mm	78	4 (2x2R)
71	35	283	P	78	6 (3x2R)
72	35	283	P / 2xperf. et	78	6 (3x2R)
73	37	70	F - (litera "D")	114	5
74	38	20	U	65	6
75	38	32	U (PK)	78	6
76	38,1	57,15	U	95	6
77	38	180	U	115	6
78	39	23	P - z perf. (owal)	78	6
79	39	60	P	79	6
80	39,1	136,5	U	88	5
81	40	ciągła	P - podcięcie podkałdu	88	2
82	40	12	F - J-407 *	65	2
83	40	15	U	67	5
84	40	16	F - nacięcie et. w 1/2 szerokości	78	1
85	40	20	U	78	5
86	40	20	F/P blac mark 2,5 mm	78	5
87	40	21	U	78	5
88	40	23	U / TYRE	66	4
89	40	25	U	95	5
90	40	25,4	KA - karton, perf. , black mark 2,5 mm	80	5
92	40	27	U	85	4
93	40	28	P	85	4
94	40	30	U / P	95	4
95	40	30	P	95	5
96	40	35	U	85	5
97	40	40	P	67	4
98	40	50	P	67	4
99	40	68	U	67	5
100	40	130	PK / 4,94mm / TYRE	85	5
101	40	204	U	65	4
102	40	210	U	67	2
103	40	210	P - (3 x perf.)	67	3
104	42	15	F	67	4
105	42	61,5	P	82	4
106	42	85	P	110	4
107	43	58	wykr. NTI		5
108	43	150	P	96	5
109	45	18	F - J-407 *	65	2
110	45	18	P	65	4
111	45	20	U	67	4
112	45	25	P	79	5
113	45	25	F	78	5
114	45	52	P	103	5

115	45	70	P	115	4 / 5
116	45	76,2	KA - karton, perf., wcięcia, dziurka	96	4
117	45	150	P	96	5
118	46	80	P	78	4
119	47	38	U	65	5
120	48	20	P	67	3
121	48	49	U	66	5
122	50	14	U - J-407 *	68	2 / 4
123	50	14	U - wcięcie etykiet w 1/2 szerokości	65	4
124	50	15	U	68	4
125	50	20	U / F	65	2 / 4
126	50	25	P	95	4
127	50	25	P	95	4
128	50	25	P - FALA	96	4
129	50	25	P black mark 3mm	96	4
130	50	30	P	95	4
131	50	30	F	82	4
132	50	30	U - J-407 *	95	2
133	50	35	U	95	4
134	50	38	KA - karton, perf. , black mark 4 mm	0	0
135	50	40	U	67	4
136	50	50	P	67	4
137	50	60	U	79	4
138	50	69,5	U	114	4
139	50	85	U	110	4
140	50	90	U	88	4
141	50	100	P	65	4
142	50	180	P	115	4
143	52	40	P	67	4
144	53	40	U	67	4
145	53	115	U	74	2
146	54	33	P	68	4
147	54	47	U - perf.	79	4
148	55	8	F	80	2
149	55	11	U - J-407 *	65	2
150	55	15	F (PK)	67	4
151	55	22	P	65	4
152	55	25	U	78	4
153	55	30	U	74	2
154	55	41,27	KA - karton perf, black mark 4 mm	78	4
155	55	46	P	78	4
156	55	50	P	67	4
157	55	66	U	65	4
158	55	80	P	78	4
159	57	43	U / P	88	4
160	58	40	P - do wag	67	4
161	58	40	F	67	4
162	58	40	KA - karton perf, black mark 4 mm	67	4
163	58	43	P / F	88	4
164	58	56	P / F	74	4
165	58	60	P / F	79	4
166	58	68	P / F	67	4
167	58	114	P - owal	74	4
168	60	9	U	65	2
169	60	12	U / J-407	66	2
170	60	12	U	78	4
171	60	12	P - nacięcie et. w 1/2 szerokości	66	4
172	60	15	P	67	4
173	60	16	U / TYRE 10tys.	66	4
174	60	20	F - J-406/407 *	78	2

175	60	25	P	95	4
176	60	25	U	95	4
177	60	30	P	95	4
178	60	30	F / TYRE	85	4
179	60	30	F	82	4
180	60	38	KA - karton, perf., black mark 4 mm		4
181	60	40	TYRE	67	3
182	60	40	F	67	2
183	60	40	F, black mark 3 mm	67	4
184	60	50	P	67	4
185	60	60	U	79	4
186	60	80	P	79	4
187	60	100	U	65	4
188	60	120	P - perf.	78	4
189	60	150	F	96	4
190	60	210	P	67	4
191	64	38	P - (3 w 1)	78	3
192	65	25	U	78	3
193	65	30	P	74	3
194	65	40	P	82	3
195	67	136	U	88	2
196	68	38	P	78	3
197	68	50	U	67	3
198	70	10	U	68	2
199	70	15	P	67	3
200	70	25	U	78	3
201	70	30	P	95	3
202	70	30	P	96	3
203	70	33	P	67	3
204	70	35	P	95	3
205	70	40	P	67	3
206	70	50	U	67	3
207	70	50	U - z perf.	67	3
208	70	60	P	79	3
209	70	70	P	115	3
210	70	70	P - z perf.	115	3
211	70	80	P	78	3
212	70	140	P	90	3
214	74	104	P - z perf.	67	3
215	74	171	P; J-407 *	110	3
217	74	210	U/P z perf.	67	3
218	74	210	P (3 w 1 - nacięcia etyk.)	67	3
219	75	17	P	95	3
220	75	25	P	95	3
221	75	35	P	95	3
222	75	35	F - J-407	95	1
223	75	50	P	67	3
224	75	50	KA - karton, perf., wcięcia	80	2
225	75	60	P	79	3
226	75	80	U	79	3
227	75	130	KA - karton, perf., wcięcia	82	3
228	75	210	KA - karton, perf., wcięcia	66	3
229	75	212	KA - karton, perf., wcięcia	67	3
230	76	ciągła	P - margines podkładu 2x	88	1
232	76	106	U	103	3
233	76	120	P	78	3
234	76	127	U	82	3
235	76	127	U, perf.	82	3
236	78	22	U	65	3

237	80	20	U	67	3
238	80	25	U	78	3
239	80	40	P	67	3 / .2
240	80	48	P, perf +naciecia 40x16	65	3
241	80	50	F - J-407 *	67	1
242	80	50	U / P	67	3
243	80	60	U	79	3
244	80	65	U	85	3
245	80	65	P	85	3
246	80	65	P	65	3
247	80	80	P	78	3
248	80	100	P	65	3
249	80	117,45	KA - karton, perf., black mark 4 mm	74	3
250	80	121	P	78	3
251	80	140	P	90	3
252	80	150	U	96	2
253	80	176	U / 4,95mm	114	3
254	83	15	U	74	2
255	85	150	U	96	2
256	87	127	U	82	2
257	88	24	U	67	2
259	90	17	F	65	2
260	90	29	U	79	2
261	90	35	F	85	2
262	90	40	F	68	2
263	90	50	U	67	2
264	90	60	U	79	2
265	90	80	U	78	2
266	90	90	P	88	2
267	90	110	P	110	2
268	90	128	U	82	2
269	92	25	U	78	2
270	100	8	F	66	2
271	100	15	U	67	2
272	100	23	F (PK)	65	2
273	100	25	U	78	2
274	100	25	U - perf.	78	2
275	100	30	U	82	3
276	100	35	P - (do pap.T)	95	2
277	100	35	P	95	2
278	100	36	U / TYRE 10tys.	85	2
279	100	36	U - z perf.	74 / 99	2
280	100	36	U - z perf.	85	1
281	100	39	U - (2 nacięcia na szerokości etykiety)	66	2
282	100	40	U	67	2
283	100	50	U	67	2
284	100	50	F	67	2
285	100	50	P - perf.	67	2
286	100	55	U	74	2
287	100	59	U	78	2
288	100	59	U - perf.	78	2
289	100	60	F	99 / 80	2
290	100	60	P - perf. + nacięcie krzyżyk	100	2
291	100	70	P / 8,31 mm	74	2
292	100	70	U - perf.	115	2
293	100	70	U / TYRE / bez perf.	115	1
294	100	75	P / U	74	2
295	100	80	U	78	2
296	100	80	U - perf.	78	2
297	100	92	F	90	2
298	100	100	P / U	65	2
299	100	100	F / TYRE 10tys.	65	2
300	100	120	U / 3,8 mm	78	2

301	100	132	U - perf.	85	2
302	100	150	U	96	2
303	100	150	P / F black mark 2,5 mm		2
304	100	150	U - perf.	96	2
305	100	150	KA - karton, perf., wcięcia, dziurka		2
306	100	150	P nacięcie 40x13mm	96	2
307	100	160	P - perf.	103	2
308	100	160	P	103	2
309	100	170	U / 4,6 mm	110	2
310	100	170	U - perf. / 4,6 mm	110	2
311	100	170	U - 2xperf.	110	2
312	100	180	U	115	2
313	100	ciągła	F - 105 mm podkład / margines 1x / 2x	65	2
314	100	ciągła	F - margines / 2x2mm	65	2
315	101,6	203,2	U	65	2
317	102	55	P - (perf.+nacięcia etyk.)	74	2
318	102	102	P	66	2
319	104	45	P	90	2
320	104	104	U	67	2
321	104	147,5	P - perf.+ składanka	95	2
322	104	153,5	F	99	2
323	105	17	U	68	2
324	105	32	U	78	2
325	105	65	P	65	2
326	105	92	U	90	2
327	105	99,3	U - perf.	65	2
328	105	148	P	95	2
329	105	148	P - perf.	95	2
330	105	171	P	110	2
331	105	210	P - perf.	67	2
332	105	230	P	74	2
333	105	251	P, perf. + składanka	80	1
335	107	76	F (PK)	74	2
336	107	140			2
337	107	150	P	96	2
338	107	178	P	114	2
339	109	150	F - (PK) / E - P	96	2
340	110	62	U	103	2
341	110	80	U	79	2
342	110	80	U - perf.	79	2
343	110	160	U	103	2
344	110	180	P	115	2
345	110	210	U	67	2
346	114	41	U	82	2
347	120	23	U	65	2
348	120	30	U	74	2
349	123	62	U	82	2
350	127	30	U	82	1
351	130	100	U - perf.	67	1
352	135	35	U	85	1
353	140	50	U	66	1
354	147	100	U	65	1
355	148	103	P - nacięcie z boku etyk.	67	1
356	148	104	P - perf.	67	1
357	148	113	P	67	1
358	148	132	U - nacięcia et. 3 w 1	85	1
359	148	210	P, arkusz	67	
360	148	210	P	67	1
361	148	210	P / U - perf.	67	1
362	148	312	KA - karton, perf., wcięcia	100	1

363	149	212	P - perf.	68	1
364	150	ciągła	P - margines 2x	65	1
365	150	70	P	115	1
366	150	179	P	115	1
367	150	210	KA - karton, perf., wcięcia	66	1
368	150	210	P - perf.	67	1
369	165	113	U	110	1
370	168	75,4	KA - karton, perf., wcięcia	95	1
372	210	ciągła	U - margines 2x ...	68	1
373	210	148	P - perf.	95	1
374	Ø 10		perf. et. - pion	68	6
375	Ø 14		F / Black mark 2,5 mm	68	6
376	Ø 18		F / Black mark 2,5 mm	67	6
377	Ø 20		F	65	4 (2x2R)
378	Ø 39		P	67	6
379	Ø 50		P	67	4
380	Ø 60		P	78	2

L. P.	Cylinder magnetyczny		
1	65	R	
2	66	RM	
3	67	S	
4	68	RM	
5	74	R	
6	78	S	
7	79	S	
8	80	Nowa	L
9	82	R	
10	85	R	
11	88	R	
12	90	R	
13	95	S	
14	96	S	
15	99	RM	
16	100	RM	
17	103	RM	
18	110	R	
19	114	R	
20	115	S	

L. P.
1
2
3
4
5
6
7

- * PRZED POTWIEF
WYKROJNIKA
- * UWAGA! TEKST
WPISANE NAWO
- * ZALEŻNOŚCI OD