

wymiar w mm szer. x wys.		Dodatkowe informacje
X	Y	
7	150	U / min. 2R
10	10	<i>P - specjalny</i>
10	12	<i>PK / min. 2rz</i>
10	100	U
10	100	<i>U - perf.</i>
12	14	F
15	5	<i>U - specjalny *</i>
15	7	U - J-407 *
15	15	F, black mark 2,5 mm
15	40	U
15	60	U
17	90	U
19	22	U
20	10	P
20	10	P/F black mark 2,5 mm
20	10	<i>F - specjalny*</i>
20	20	U
20	40	<i>P - odstęp między rzędami 40mm</i>
20	80	F
21	40	U
22	7	P
22	50	P
23	12,3	U
23	120	U
23	150	P
25	15	F - specjalny *
25	15	U
25	25	U
25	25	<i>U - z perf. etykiety</i>
25	35	U
25	40	U
25	75	U
25	80	U
26	9	F
26	14	P
30	11	U
30	11	F - specjalny *
30	12	U
30	12	<i>F - nacięcie etykiet</i>
30	15	U
30	17	U
30	20	P
30	20	P - specjalny
30	30	F
30	30	U / perf. pion
30	40	P
30	60	U
30	80	P
30	127,5	P
30	180	P
31	22	T
32	15	U
32	20	U / TYRE 10tys.
32	20	U/F (PK)
32	25	U

32	35	P
32	40	U
34	20	U
34	70	P
33	16	F
35	14	F
35	25	P
35	30	P
35	40	P
35	50	U (PK)
35	59	P
35	243	P / 4,65 mm
35	283	P
35	283	P / 2xperf. et
37	70	F - (litera "D")
38	32	U (PK)
38,1	57,15	U
38	180	U
39	23	P - z perf. (owal)
39	60	P
40	ciągła	P - podcięcie podkałdu
40	12	F - J-407 *
40	15	U
40	16	F - nacięcie etykiet
40	20	U
40	20	F/P blac mark 2,5 mm
40	21	U
40	23	U / TYRE
40	25	U
40	25,4	KA - karton, perf. , black mark 2,5 mm
40	27	U
40	28	P
40	30	U
40	30	P
40	35	U
40	40	P
40	50	P
40	68	U
40	130	PK / 4,94mm / TYRE
40	204	U
40	210	U
40	210	P - (3 x perf.)
42	15	F
42	61,5	P
42	85	P
43	150	P
45	18	F - J-407 *
45	18	P
45	20	U
45	25	P
45	25	F
45	52	P
45	70	P
45	76,2	KA - karton, perf., wcięcia, dziurka
45	150	P
46	80	P
48	20	P
48	49	U
50	14	U - J-407 *
50	14	U - nacięcie etykiet
50	15	U
50	20	U / F
50	25	P

50	25	P
50	25	P - FALA
50	30	P
50	30	F
50	30	U - J-407 *
50	35	U
50	40	U
50	50	P
50	60	U
50	69,5	U
50	85	U
50	90	U
50	100	P
50	180	P
52	40	P
53	40	U
53	115	U
54	33	P
54	47	U - perf.
55	8	F
55	11	U - J-407 *
55	15	F (PK)
55	22	P
55	25	U
55	30	U
55	46	P
55	50	P
55	66	U
55	80	P
57	43	U / P
58	40	P - do wag
58	40	F
58	43	P / F
58	56	P / F
58	60	P / F
58	68	P / F
58	114	P - owal
60	9	U
60	12	U / J-407
60	12	U
60	12	P - nacięcie w szerokości 1/2
60	15	P
60	16	U / TYRE 10tys.
60	20	F - J-406/407 *
60	25	P
60	25	U
60	30	P
60	30	F / TYRE
60	30	F
60	38	KA, perf. , mark black
60	40	TYRE
60	40	F
60	40	F
60	50	P
60	60	U
60	80	P
60	100	U
60	150	F
60	210	P
64	38	P - ( 3 w 1 )
65	25	U
65	30	P
65	40	P
67	136	U

68	38	P
68	50	U
70	10	U
70	15	P
70	25	U
70	30	P
70	33	P
70	35	P
70	40	P
70	50	U
70	50	U - z perf.
70	60	P
70	70	P
70	70	P - perforacja
70	80	P
70	140	P
74	104	P z perf.
74	171	P; J-407 *
74	210	U/P z perf.
74	210	<i>P ( 3 w 1 - nacięcia etyk.)</i>
75	17	P
75	25	P
75	35	P
75	35	F - J-407
75	50	P
75	60	P
75	80	U
75	130	<i>KA - karton, perf., wcięcia</i>
75	210	<i>KA - karton, perf., wcięcia</i>
75	212	<i>KA - karton, perf., wcięcia</i>
76	ciągła	<i>P - margines podkładu 2x</i>
76	106	U
76	120	P
76	127	U
78	22	U
80	20	U
80	25	U
80	40	P
80	50	F - specjalny *
80	50	U / P
80	60	U
80	65	U
80	65	P
80	65	P
80	80	P
80	100	P
80	117,45	KA, perforacja, black mark
80	121	P
80	140	P
80	150	U
80	176	U
83	15	U
85	150	U
87	127	U
88	24	U
90	17	F
90	29	U
90	35	F
90	40	F
90	50	U
90	60	U
90	90	P
90	110	P
90	128	U

92	25	U
100	8	F
100	15	U
100	23	F (PK)
100	25	U
100	30	U
100	35	P - (do pap.T)
100	35	P
100	36	U - specjalny
100	36	U - z perf.
100	36	U - z perf.
100	39	<i>U - (2 nacięcia na szerokości etykiety)</i>
100	40	U
100	50	U
100	50	F
100	50	P - perf.
100	55	U
100	59	U
100	59	U - perf.
100	60	F
100	70	P / 8,31 mm
100	70	U - perf.
100	70	specjalny
100	75	P / U
100	80	U
100	80	U - perf.
100	92	F
100	100	P / U
100	100	F - specjalny
100	120	U / 3,8 mm
100	132	U - perf.
100	150	U
100	150	P / F black mark 2,5 mm
100	150	U - perf.
100	150	KA karton, perf., wcięcia, dziurka
100	160	P - perf.
100	160	P
100	170	U / 4,6 mm
100	170	U - perf. / 4,6 mm
100	170	U - 2xperf.
100	180	U
100	ciągła	F - 105 mm podkład / margines 1x / 2x
102	55	<i>P - (perf.+nacięcia etyk.)</i>
102	102	P
104	45	P
104	104	U
104	147,5	P - perf.+ składanka
104	153,5	F
105	17	U
105	32	U
105	65	P
105	92	U
105	99,3	U - perf.
105	148	P
105	148	P - perf.
105	171	P
105	210	P - perf.
105	230	P
105	251	P, perf. + składanka
107	76	F (PK)
107	150	P
107	178	P
109	150	F - (PK) / E - P
110	62	U

110	80	U
110	80	U - perf.
110	180	P
110	210	U
114	41	U
120	23	U
123	62	U
127	30	U
130	100	U - perf.
135	35	U
140	50	U
147	100	U
148	103	<i>P - nacięcie z boku etyk.</i>
148	104	P - perf.
148	113	P
148	132	<i>U - nacięcia et. 3 w 1</i>
148	210	P, arkusz
148	210	P
148	210	<i>P / U - perf.</i>
148	312	<i>KA - karton, perf., wcięcia</i>
149	212	P - perf.
150	ciągła	P - margines 2x
150	70	P
150	210	<i>KA - karton, perf., wcięcia</i>
165	113	U
210	ciągła	U - margines 2x
210	148	P - perf.
Ø 10		perf. et. - pion
Ø 14		F
Ø 18		F
Ø 20		F
Ø 39		P
Ø 50		P
Ø 60		P

Cylinder magnetyczny		
65		R
66		RM
67		S
68		RM
74		R
78		S
79		S
80	Nowa	L
82		R
85		R
88		R
90		R
95		S
96		S
99		RM

100		RM
103		RM
110		R
114		R
115		S